

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
LED HIGH BAY LUMINAIRES									
PHB High Performance LED High Bay									
PHB-4FT-6-320-120M	PHB LED HIGH BAY 4FT	OPT DIM	**						
PHB-4FT-6-320-347	PHB LED HIGH BAY 4FT	OPT DIM	**						
PHB-4FT-4-220-120M	PHB LED HIGH BAY 4FT	OPT DIM	**						
PHB-4FT-4-220-347	PHB LED HIGH BAY 4FT	OPT DIM	**						
PHB-2FT-6-160-120M	PHB LED HIGH BAY 2FT	OPT DIM	**						
PHB-2FT-6-160-347	PHB LED HIGH BAY 2FT	OPT DIM	**						
PHB-2FT-4-110-120M	PHB LED HIGH BAY 2FT	OPT DIM	**						
PHB-2FT-4-110-347	PHB LED HIGH BAY 2FT	OPT DIM	**						
BLACKSTAR - CHB Circular LED High Bay									
CHB 5000K STANDARD CLEAR LENS									
CHB-100LED50K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-100LED50K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED50K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED50K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED50K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED50K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB 4000K STANDARD CLEAR LENS									
CHB-100LED40K-120M 100839	LED CIRCULAR HIGH BAY 100W, 4000K, 120-277V, CLEAR LENS, BEAM ANGLE 120°	Non-Dim							
CHB-100LED40K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
CHB-100LED40K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED40K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED40K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED40K-120M-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED40K-347-D	LED CIRCULAR HIGH BAY CLEAR LENS, BEAM ANGLE 120°	DIM	X						
CHB 5000K FROSTED LENS									
CHB-100LED50K-120M-D(FL)	LED CIRCULAR HIGH BAY 100W, 5000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-100LED50K-347-D(FL)	LED CIRCULAR HIGH BAY 100W, 5000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED50K-120M-D(FL)	LED CIRCULAR HIGH BAY 150W, 5000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED50K-347-D(FL)	LED CIRCULAR HIGH BAY 150W, 5000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED50K-120M-D(FL)	LED CIRCULAR HIGH BAY 250W, 5000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED50K-347-D(FL)	LED CIRCULAR HIGH BAY 250W, 5000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB 4000K FROSTED LENS									
CHB-100LED40K-120M-D(FL)	LED CIRCULAR HIGH BAY 100W, 4000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
CHB-100LED40K-347-D(FL)	LED CIRCULAR HIGH BAY 100W, 4000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED40K-120M-D(FL)	LED CIRCULAR HIGH BAY 150W, 4000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-150LED40K-347-D(FL)	LED CIRCULAR HIGH BAY 150W, 4000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED40K-120M-D(FL)	LED CIRCULAR HIGH BAY 250W, 4000K, 120-277V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
CHB-250LED40K-347-D(FL)	LED CIRCULAR HIGH BAY 250W, 4000K, 180-528V, DIMMABLE, FROSTED LENS, BEAM ANGLE 120°	DIM	X						
BLACKSTAR E - CHBU Circular LED High Bay Extreme									
CHBU 5000K STANDARD CLEAR LENS									
CHBU-100W-110-H-50K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-100W-110-H-50K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-150W-110-H-50K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-150W-110-H-50K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-200W-110-H-50K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-200W-110-H-50K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU 4000K STANDARD CLEAR LENS									
CHBU-100W-110-H-40K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						

DIMMER COMPATIBILITY LIST



**** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor**

X Standard Product

			0-10V 120-277V	120V	120V	120V	120V	120V	120V
Model#	Product Description	Dimmable	Diva-DVSTV	MRF2S-6ND-120	CTCL-150	PD-6WCL	DVELV-300P	DVCL-153P	PD-5NE
CHBU-100W-110-H-40K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-150W-110-H-40K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-150W-110-H-40K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-200W-110-H-40K	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
CHBU-200W-110-H-40K-HV	LED CIRCULAR HIGH BAY EXTREME CLEAR LENS, BEAM ANGLE 110° IP66 NEMA 4X NSF	DIM	X						
NEBULA - CHBR Circular LED High Bay Ring									
CHBR 5000K									
CHBR-150W-120-H-50K	LED CIRCULAR HIGH BAY RING BEAM ANGLE 120° IP66 NEMA 4X NSF	DIM	X						
CHBR-150W-120-H-50K-HV	LED CIRCULAR HIGH BAY RING BEAM ANGLE 120° IP66 NEMA 4X NSF	DIM	X						
CHBR 4000K									
CHBR-150W-120-H-40K	LED CIRCULAR HIGH BAY RING BEAM ANGLE 120° IP66 NEMA 4X NSF	DIM	X						
CHBR-150W-120-H-40K-HV	LED CIRCULAR HIGH BAY RING BEAM ANGLE 120° IP66 NEMA 4X NSF	DIM	X						
NEBULA - CHBD Circular LED High Bay Dome									
CHBD 4000K									
CHBD-150W-120-H-40K	LED CIRCULAR HIGH BAY DOME BEAM ANGLE 120° IP69K NEMA 4X NSF	DIM	X						
CHBD-150W-120-H-40K-HV	LED CIRCULAR HIGH BAY DOME BEAM ANGLE 120° IP69K NEMA 4X NSF	DIM	X						
CHBD 3000K									
CHBD-150W-120-H-30K	LED CIRCULAR HIGH BAY DOME BEAM ANGLE 120° IP69K NEMA 4X NSF	DIM	X						
CHBD-150W-120-H-30K-HV	LED CIRCULAR HIGH BAY DOME BEAM ANGLE 120° IP69K NEMA 4X NSF	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
LED Linear High Bay									
LHB 5000K BEAM STANDARD TYPE V									
LHB-100LED-50K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-100LED-50K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-150LED-50K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-150LED-50K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-200LED-50K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-240LED-50K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-240LED-50K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB 4000K BEAM STANDARD TYPE V									
LHB-100LED-40K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-100LED-40K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-150LED-40K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-150LED-40K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-200LED-40K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-240LED-40K-120M-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LHB-240LED-40K-347-V-D	LED LINEAR HIGH BAY BEAM TYPE V (120°)	DIM	X						
LED Gym Lume									
GL16LED16-120M (P)	PREMIUM LED GYM LUME	OPT DIM	**						
GL16LED16-347 (P)	PREMIUM LED GYM LUME	OPT DIM	**						
GL80LED08-120M (P)	PREMIUM LED GYM LUME	OPT DIM	**						
GL80LED08-347 (P)	PREMIUM LED GYM LUME	OPT DIM	**						
LED High Bay Vapor Tight									
VTHB22LED04-120M	LED HIGH BAY VAPOR TIGHT	OPT DIM	**						
VTHB22LED04-347	LED HIGH BAY VAPOR TIGHT	OPT DIM	**						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
VTHB16LED03-120M	LED HIGH BAY VAPOR TIGHT	OPT DIM	**						
VTHB16LED03-347	LED HIGH BAY VAPOR TIGHT	OPT DIM	**						
LED VAPOR TIGHT LUMINAIRE									
ORIGINAL STYLE VAPOR TIGHTS									
VT54LED04-120M (P)	PREMIUM LED VAPOR TIGHT 4FT IP65 STANDARD OPAL LENS	OPT DIM	**						
VT54LED04-347 (P)	PREMIUM LED VAPOR TIGHT 4FT IP65 STANDARD OPAL LENS	OPT DIM	**						
VT80LED08-120M (P)	PREMIUM LED VAPOR TIGHT 4FT IP65 STANDARD OPAL LENS	OPT DIM	**						
VT80LED08-347 (P)	PREMIUM LED VAPOR TIGHT 4FT IP65 STANDARD OPAL LENS	OPT DIM	**						
NEW DESIGN VAPOUR TIGHTS									
VT40LED04-120M (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 3.5" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT40LED04-347 (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 3.5" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT54LED04-120M (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 4" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT54LED04-347 (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 4" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT54LED04-120M/347 (P) BN	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 4.5" (W) IP66 NEMA 4X STANDARD FROSTED ETCHED LENS	DIM	X						
VT54LED04-120M (P) BW	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 6.5" (W) WIDE BODY IP65 STANDARD OPAL LENS	DIM	X						
VT54LED04-347 (P) BW	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 6.5" (W) WIDE BODY IP65 STANDARD OPAL LENS	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
VT80LED08-120M (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 6.5" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT80LED08-347 (P) B	PREMIUM LED VAPOUR TIGHT B DESIGN 4FT 6.5" (W) IP65 STANDARD FROSTED ETCHED LENS	OPT DIM	**						
VT8N-120LED50K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 4" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8N-120LED40K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 4" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8N-120LED50K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 4" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8N-120LED40K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 4" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8W-160LED50K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 6.3" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8W-160LED40K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 6.3" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8W-160LED50K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 6.3" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT8W-160LED40K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 8FT 6.3" (W) IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT24-120LED50K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 2'x4' IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT24-120LED40K-120M	PREMIUM LED VAPOUR TIGHT B DESIGN 2'x4' IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT24-120LED50K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 2'x4' IP65 FROSTED ETCHED LENS ONLY	DIM	X						
VT24-120LED40K-347	PREMIUM LED VAPOUR TIGHT B DESIGN 2'x4' IP65 FROSTED ETCHED LENS ONLY	DIM	X						
LED TROFFER LUMINAIRES									
LED Panel Light									
PL14-40LED-120M	LED PANEL LIGHT 1x4	DIM	X						
PL14-40LED-347	LED PANEL LIGHT 1x4	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

			Diva-DVSTV	MRF2S-6ND-120	CTCL-150	PD-6WCL	DVELV-300P	DVCL-153P	PD-5NE
Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
PL22-40LED-120M	LED PANEL LIGHT 2x2	DIM	X						
PL22-40LED-347	LED PANEL LIGHT 2x2	DIM	X						
PL24-50LED-120M	LED PANEL LIGHT 2x4	DIM	X						
PL24-50LED-347	LED PANEL LIGHT 2x4	DIM	X						
PL24-60LED-120M/347	LED PANEL LIGHT 2x4	DIM	X						
LED Panel Light E									
PLE 3500K									
PLE14-36LED-120-347 (3.5K)	LED ECONOMY PANEL LIGHT 1x4	DIM***	X						
PLE22-36LED-120-347 (3.5K)	LED ECONOMY PANEL LIGHT 2x2	DIM***	X						
PLE24-50LED-120-347 (3.5K)	LED ECONOMY PANEL LIGHT 2x4	DIM***	X						
PLE 4000K									
PLE14-36LED-120-347 (4K)	LED ECONOMY PANEL LIGHT 1x4	DIM***	X						
PLE22-36LED-120-347 (4K)	LED ECONOMY PANEL LIGHT 2x2	DIM***	X						
PLE24-50LED-120-347 (4K)	LED ECONOMY PANEL LIGHT 2x4	DIM***	X						
PLE 5000K									
PLE14-36LED-120-347 (5K)	LED ECONOMY PANEL LIGHT 1x4	DIM***	X						
PLE22-36LED-120-347 (5K)	LED ECONOMY PANEL LIGHT 2x2	DIM***	X						
PLE24-50LED-120-347 (5K)	LED ECONOMY PANEL LIGHT 2x4	DIM***	X						
LED TC-II Troffer									
TC-II-22-30W-35K-MV	TC-II CENTRE BASKET TROFFER 2x2	DIM	X						
TC-II-22-30W-40K-MV	TC-II CENTRE BASKET TROFFER 2x2	DIM	X						
TC-II-22-30W-50K-MV	TC-II CENTRE BASKET TROFFER 2x2	DIM	X						
TC-II-24-40W-35K-MV	TC-II CENTRE BASKET TROFFER 2x4	DIM	X						
TC-II-24-40W-40K-MV	TC-II CENTRE BASKET TROFFER 2x4	DIM	X						
TC-II-24-40W-50K-MV	TC-II CENTRE BASKET TROFFER 2x4	DIM	X						

***For applications where dimming is intended, note that capacitor(s) may be required for optimal dimming performance depending on the controller used.

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
LED TC Troffer									
TC40LED02-120M (P)	PREMIUM LED 2x2 DECORATIVE TROFFER	OPT DIM	**						
TC40LED02-347 (P)	PREMIUM LED 2x2 DECORATIVE TROFFER	OPT DIM	**						
TC54LED04-120M (P)	PREMIUM LED 2x4 DECORATIVE TROFFER	OPT DIM	**						
TC54LED04-347 (P)	PREMIUM LED 2x4 DECORATIVE TROFFER	OPT DIM	**						
LED TD Troffer									
TD14-40LED02-120M (P)	PREMIUM LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD14-40LED02-347 (P)	PREMIUM LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD14-40LED02-120M	LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD14-40LED02-347	LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD14-40LED04-120M	LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD14-40LED04-347	LED 1 x 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD54LED04-120M	LED 2 X 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
TD54LED04-347	LED 2 X 4 DIRECT/INDIRECT LIGHT TROFFER	OPT DIM	**						
LED TF-SS Troffer									
TF14-40LED02-SS-120M	LED 1 x 4 TF-SS TROFFER	OPT DIM	**						
TF14-40LED02-SS-347	LED 1 x 4 TF-SS TROFFER	OPT DIM	**						
TF40LED02-SS-120M	LED 2 x 2 TF-SS TROFFER	OPT DIM	**						
TF40LED02-SS-347	LED 2 x 2 TF-SS TROFFER	OPT DIM	**						
LED STRIP FIXTURES									
LED Stream Flow Strip II									
SF-II 4000K									
SF-II-2-20W40K-MV	LED STREAM FLOW STRIP II 2FT	DIM	X						
SF-II-4-32W40K-MV	LED STREAM FLOW STRIP II 4FT	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

			Diva-DVSTV	MRF2S-6ND-120	CTCL-150	PD-6WCL	DVELV-300P	DVCL-153P	PD-5NE
Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
SF-II-4-40W40K-MV	LED STREAM FLOW STRIP II 4FT	DIM	X						
SF-II-8-64W40K-MV	LED STREAM FLOW STRIP II 8FT	DIM	X						
SF-II-8-80W40K-MV	LED STREAM FLOW STRIP II 8FT	DIM	X						
SF-II 5000K									
SF-II-2-20W50K-MV	LED STREAM FLOW STRIP II 2FT	DIM	X						
SF-II-4-32W50K-MV	LED STREAM FLOW STRIP II 4FT	DIM	X						
SF-II-4-40W50K-MV	LED STREAM FLOW STRIP II 4FT	DIM	X						
SF-II-8-64W50K-MV	LED STREAM FLOW STRIP II 8FT	DIM	X						
SF-II-8-80W50K-MV	LED STREAM FLOW STRIP II 8FT	DIM	X						
LED Stream Flow Strip									
SF2-40LED02-120M	LED STREAM FLOW STRIP 2FT	OPT DIM	**						
SF2-40LED02-347	LED STREAM FLOW STRIP 2FT	OPT DIM	**						
SF3-40LED03-120M	LED STREAM FLOW STRIP 3FT	OPT DIM	**						
SF3-40LED03-347	LED STREAM FLOW STRIP 3FT	OPT DIM	**						
SF4-40LED04-120M (P)	PREMIUM LED STREAM FLOW STRIP 4FT	OPT DIM	**						
SF4-40LED04-347 (P)	PREMIUM LED STREAM FLOW STRIP 4FT	OPT DIM	**						
LED Flex Stream Linear Strip									
FS4-40LED02-120M (P)	PREMIUM LED FLEX STREAM STRIP 4FT	OPT DIM	**						
FS4-40LED02-347 (P)	PREMIUM LED FLEX STREAM STRIP 4FT	OPT DIM	**						
FS4-40LED04-120M (P)	PREMIUM LED FLEX STREAM STRIP 4FT	OPT DIM	**						
FS4-40LED04-347 (P)	PREMIUM LED FLEX STREAM STRIP 4FT	OPT DIM	**						
FS8-54LED04-120M (P)	PREMIUM LED FLEX STREAM STRIP 8FT	OPT DIM	**						
FS8-54LED04-347 (P)	PREMIUM LED FLEX STREAM STRIP 8FT	OPT DIM	**						
FS8-80LED08-120M (P)	PREMIUM LED FLEX STREAM STRIP 8FT	OPT DIM	**						
FS8-80LED08-347 (P)	PREMIUM LED FLEX STREAM STRIP 8FT	OPT DIM	**						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
WS-P2028-LED	LED WALL SCONCE BN, WH GLASS LENS 7.9"	DIM		X	X	X	X	X	X
LED Flush Mount Ceiling Light									
CL-A9802-LED04-120	LED FLUSH MOUNT ROUND BN+WH 18"	DIM		X	X	X	X	X	X
CL-A9802A-LED03-120	LED FLUSH MOUNT ROUND BN+WH 14"	DIM		X	X	X	X	X	X
CL-A9802B-LED02-120	LED FLUSH MOUNT ROUND BN+WH 10.3"	DIM		X	X	X	X	X	X
CL-A6111-6-LED02-120	LED FLUSH MOUNT ROUND WHITE 11"	DIM		X	X	X	X	X	X
CL-T6113-6-LED03-120M	LED FLUSH MOUNT ROUND WHITE 14"								
CL-A6211-6-LED02-120	LED FLUSH MOUNT ROUND WHITE 11"	DIM		X	X	X	X	X	X
CL-T6213-6-LED03-120M	LED FLUSH MOUNT ROUND WHITE 14"								
CL-T6513-6-LED04-120M	LED FLUSH MOUNT SQUARE WHITE 15"								
CL-T6512-6-LED04-120M	LED FLUSH MOUNT SQUARE WHITE 12"								
LED CANOPY AND GARAGE LIGHTING									
LED Garage Lighter									
GARAGE LIGHTER									
GA40LED04-120M (Q)	LED GARAGE LIGHTER WITH QUICK INSTALLATION PLATE	OPT DIM	**						
GA40LED04-347 (Q)	LED GARAGE LIGHTER WITH QUICK INSTALLATION PLATE	OPT DIM	**						
GA-60LED50K-120M	LED GARAGE LIGHTER	OPT DIM	**						
GA-60LED50K-347	LED GARAGE LIGHTER	OPT DIM	**						
LED OUTDOOR LIGHTING									
LED Flood Light									
ARCHITECTURAL FLOOD LIGHT 5000K WITHOUT MOUNTING ACCESSORIES									
AFL-90LED-50K-120M	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-90LED-50K-347	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-180LED-50K-120M	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-180LED-50K-347	ARCHITECTURAL FLOOD LIGHT	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
ARCHITECTURAL FLOOD LIGHT 4000K WITHOUT MOUNTING ACCESSORIES									
AFL-90LED-40K-120M	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-90LED-40K-347	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-180LED-40K-120M	ARCHITECTURAL FLOOD LIGHT	DIM	X						
AFL-180LED-40K-347	ARCHITECTURAL FLOOD LIGHT	DIM	X						
LED Wall Pack									
WALL PACK 5000K									
WHLF-45LED50K-120M	LED HLF WALL PACK	DIM	X						
WHLF-45LED50K-347	LED HLF WALL PACK	DIM	X						
WHLF-60LED50K-120M	LED HLF WALL PACK	DIM	X						
WHLF-60LED50K-347	LED HLF WALL PACK	DIM	X						
WHLF-75LED50K-120M	LED HLF WALL PACK	DIM	X						
WHLF-75LED50K-347	LED HLF WALL PACK	DIM	X						
WALL PACK 4000K									
WHLF-45LED40K-120M	LED HLF WALL PACK	DIM	X						
WHLF-45LED40K-347	LED HLF WALL PACK	DIM	X						
WHLF-60LED40K-120M	LED HLF WALL PACK	DIM	X						
WHLF-60LED40K-347	LED HLF WALL PACK	DIM	X						
WHLF-75LED40K-120M	LED HLF WALL PACK	DIM	X						
WHLF-75LED40K-347	LED HLF WALL PACK	DIM	X						
TRAPEZOID WALL PACK 5000K									
	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-45LED50K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-60LED50K-120M	LED HLF WALL PACK TRAPEZOID	DIM	X						

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
TWHLF-60LED50K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-75LED50K-120M	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-75LED50K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
TRAPEZOID WALL PACK 4000K									
TWHLF-45LED40K-120M	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-45LED40K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-60LED40K-120M	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-60LED40K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-75LED40K-120M	LED HLF WALL PACK TRAPEZOID	DIM	X						
TWHLF-75LED40K-347	LED HLF WALL PACK TRAPEZOID	DIM	X						
SLIM WALL PACK 5000K									
SLWP-25LED-50K-120M	SLIM LED WALL PACK								
SLWP-35LED-50K-120M	SLIM LED WALL PACK	OPT DIM	**						
SLWP-35LED-50K-347	SLIM LED WALL PACK	OPT DIM	**						
SLIM WALL PACK 4000K									
SLWP-25LED-40K-120M	SLIM LED WALL PACK								
SLWP-35LED-40K-120M	SLIM LED WALL PACK	OPT DIM	**						
SLWP-35LED-40K-347	SLIM LED WALL PACK	OPT DIM	**						
LED RETROFIT KITS									
LED Q KIT									
Q KIT 3000K									

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
QF1500/30-8R-120-TD	Q KIT 8" RECTANGULAR	DIM		X	X	X	X	X	X
QF1500/30-7SC-120-TD	Q KIT 7" SEMI-CIRCULAR	DIM		X	X	X	X	X	X
QF1500/30-8C-120-TD	Q KIT 8" CIRCULAR	DIM		X	X	X	X	X	X
QF2700/30-10C-120-TD	Q KIT 10" CIRCULAR	DIM		X	X	X	X	X	X
Q KIT 4000K									
QF1500/40-8R-120-TD	Q KIT 8" RECTANGULAR	DIM		X	X	X	X	X	X
QF1500/40-7SC-120-TD	Q KIT 7" SEMI-CIRCULAR	DIM		X	X	X	X	X	X
QF1500/40-8C-120-TD	Q KIT 8" CIRCULAR	DIM		X	X	X	X	X	X
QF2700/40-10C-120-TD	Q KIT 10" CIRCULAR	DIM		X	X	X	X	X	X
LED Strip Retrofit									
SR4-40LED02-120M (P)	PREMIUM LED STRIP RETROFIT 4FT	OPT DIM	**						
SR4-40LED02-347 (P)	PREMIUM LED STRIP RETROFIT 4FT	OPT DIM	**						
SR4-40LED04-120M (P)	PREMIUM LED STRIP RETROFIT 4FT	OPT DIM	**						
SR4-40LED04-347 (P)	PREMIUM LED STRIP RETROFIT 4FT	OPT DIM	**						
SR8-54LED04-120M (P)	PREMIUM LED STRIP RETROFIT 8FT	OPT DIM	**						
SR8-54LED04-347 (P)	PREMIUM LED STRIP RETROFIT 8FT	OPT DIM	**						
SR8-80LED08-120M (P)	PREMIUM LED STRIP RETROFIT 8FT	OPT DIM	**						
SR8-80LED08-347 (P)	PREMIUM LED STRIP RETROFIT 8FT	OPT DIM	**						
LED Wraparound Retrofit									
STR40LED02-120M (P)	PREMIUM LED STR WRAP AROUND RETROFIT	OPT DIM	**						
STR40LED02-347 (P)	PREMIUM LED STR WRAP AROUND RETROFIT	OPT DIM	**						
LED Troffer Retrofit									
RF14-40LED02-120M (P)	PREMIUM LED 1 X 4 TROFFER RETROFIT	OPT DIM	**						
RF14-40LED02-347 (P)	PREMIUM LED 1 X 4 TROFFER RETROFIT	OPT DIM	**						
RF14-40LED02-120M	LED 1 X 4 TROFFER RETROFIT	OPT DIM	**						
RF14-40LED02-347	LED 1 X 4 TROFFER RETROFIT	OPT DIM	**						

DIMMER COMPATIBILITY LIST



**** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor**

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
			Divav-DVSTV	MRF2S-6ND-120	CTCL-150	PD-6WCL	DVELV-300P	DVCL-153P	PD-5NE
UTLED-S9W-4KBK-SQ	ULTRATHIN 4" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-S12W-4KBK-SQ	ULTRATHIN 4" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-S9W-4KBN-SQ	ULTRATHIN 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
UTLED-S12W-4KBN-SQ	ULTRATHIN 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
Square 6" 3000K									
UTLED-6-S12W-3KWH-SQ	ULTRATHIN 6" WHITE SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-3KWH-SQ	ULTRATHIN 6" WHITE SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S12W-3KBK-SQ	ULTRATHIN 6" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-3KBK-SQ	ULTRATHIN 6" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S12W-3KBN-SQ	ULTRATHIN 6" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-3KBN-SQ	ULTRATHIN 6" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
Square 6" 4000K									
UTLED-6-S12W-4KWH-SQ	ULTRATHIN 6" WHITE SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-4KWH-SQ	ULTRATHIN 6" WHITE SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S12W-4KBK-SQ	ULTRATHIN 6" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-4KBK-SQ	ULTRATHIN 6" BLACK SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S12W-4KBN-SQ	ULTRATHIN 6" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
UTLED-6-S15W-4KBN-SQ	ULTRATHIN 6" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
UltraThin LED Recessed Gimbal									
Round 3" 3000K									
UTLED-3-S6W-3KWH-G	ULTRATHIN GIMBAL 3" WHITE ROUND	DIM		X	X	X	X	X	X
UTLED-3-S6W-3KBK-G	ULTRATHIN GIMBAL 3" BLACK ROUND	DIM		X	X	X	X	X	X
UTLED-3-S6W-3KBN-G	ULTRATHIN GIMBAL 3" BRUSHED NICKEL ROUND	DIM		X	X	X	X	X	X
Round 3" 4000K									
UTLED-3-S6W-4KWH-G	ULTRATHIN GIMBAL 3" WHITE ROUND	DIM		X	X	X	X	X	X

DIMMER COMPATIBILITY LIST



** Standard driver in fixture needs to be changed to a dimmable driver to be able to use dimming sensor

X Standard Product

Model#	Product Description	Dimmable	0-10V 120-277V	120V	120V	120V	120V	120V	120V
RF-UTLED-S12W-4KBN	ULTRATHIN RETROFIT 4" BRUSHED NICKEL ROUND	DIM		X	X	X	X	X	X
Round 6" 3000K									
RF-UTLED-6-S12W-3KWH	ULTRATHIN RETROFIT 6" WHITE ROUND	DIM		X	X	X	X	X	X
RF-UTLED-6-S15W-3KWH (SOLD OUT)	ULTRATHIN RETROFIT 6" WHITE ROUND	DIM		X	X	X	X	X	X
Round 6" 4000K									
RF-UTLED-6-S12W-4KWH	ULTRATHIN RETROFIT 6" WHITE ROUND	DIM		X	X	X	X	X	X
RF-UTLED-6-S15W-4KWH (SOLD OUT)	ULTRATHIN RETROFIT 6" WHITE ROUND	DIM		X	X	X	X	X	X
Square 4" 3000K									
RF-UTLED-S9W-3KWH-SQ	ULTRATHIN RETROFIT 4" WHITE SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-3KWH-SQ	ULTRATHIN RETROFIT 4" WHITE SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S9W-3KKBK-SQ	ULTRATHIN RETROFIT 4" BLACK SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-3KKBK-SQ	ULTRATHIN RETROFIT 4" BLACK SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S9W-3KBN-SQ	ULTRATHIN RETROFIT 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-3KBN-SQ	ULTRATHIN RETROFIT 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
Square 4" 4000K									
RF-UTLED-S9W-4KWH-SQ	ULTRATHIN RETROFIT 4" WHITE SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-4KWH-SQ	ULTRATHIN RETROFIT 4" WHITE SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S9W-4KKBK-SQ	ULTRATHIN RETROFIT 4" BLACK SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-4KKBK-SQ	ULTRATHIN RETROFIT 4" BLACK SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S9W-4KBN-SQ	ULTRATHIN RETROFIT 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
RF-UTLED-S12W-4KBN-SQ	ULTRATHIN RETROFIT 4" BRUSHED NICKEL SQUARE	DIM		X	X	X	X	X	X
UltraThin LED Recessed Gimbal Retrofit									
Round 4" 3000K									

